

PURO LP-65

Discrete 6.5" In-Ceiling Loudspeaker

- Low profile baffle, 3.8mm grille, trim look
- Configuration : Coaxial 2 way 6.5" recess flush mount speaker
- Woofer : 6.5" PP cone with UV treated foam surround, 1" voice coil
- Tweeter : 13mm Mylar dome with capacitor protection
- Frequency Response : 55Hz ~ 22KHz
- Sensitivity : 88dB at 1w/1m
- Power Handling : 80 watts RMS, 125 watts max peak
- Nominal Impedance : 8 ohms
- Connection terminals : Spring Loaded
- Grille : 3.8mm Low profile treated steel, magnetic attachment
- Cutout hole size : 8" (204mm)
- Speaker diameter with grille fitted : 8:97" (228mm)
- Depth : 2.95" (75mm)
- Weight : Pair packed - 6.6 lbs (3kgs)
- Pair Pack Carton Dimensions : 301mm x 276mm x 302mm
- Cutout template included

nordkraft

1 Year Limited Warranty

nordkraft will repair or replace any defect in material or workmanship which occurs during normal use of this product with new or rebuilt parts, free of charge, for 1 year from the date of original purchase. This is a no hassle warranty with no mail in warranty card needed. This warranty does not cover damages in shipment, failures caused by other products not supplied by nordkraft or failures due to accident, misuse, abuse, or alteration of the product. This warranty is extended only to the original purchaser, and a purchase receipt, invoice, or other proof of original purchase date will be required before warranty repairs are provided.

This warranty gives you specific legal rights and you may have other rights (which vary from state to state). If a problem with the product develops during or after the warranty period, please contact nordkraft or your dealer or any dealer authorized service center.

Manufactured in China under strict supervision

nordkraft

PURO LP-65

Discrete 6.5" In-Ceiling Loudspeaker



www.nordkraft.systems